

## *Automatic Levels SAL*

**Fast aperture**

**Magnetically dampened compensator**



**Sturdy metal housing with rubber reinforcement**



Large focusing knob



Fine motion knobs on both sides  
with friction-braked rotation



Circular vial with penta prism



Technical specifications	SAL20ND	SAL24ND	SAL28ND	SAL32ND
<b>Part number</b>	<b>F 034 068 1N7</b>	<b>F 034 068 400</b>	<b>F 034 068 A17</b>	<b>F 034 068 200</b>
Unit of measure	Degrees	Degrees	Degrees	Degrees
Magnification	20x	24x	28x	32x
Working range	60 m	90 m	106 m	121 m
Levelling accuracy	0.1 mm/m	0.05 mm/m	0.05 mm/m	0.05 mm/m
Setting accuracy	0,8"	0,8"	0,5"	0,3"
Standard deviation for 1 km double-run leveling	2.5 mm	2.0 mm	1.5 mm	1.5 mm
Clear objective aperture	36 mm	36 mm	40 mm	40 mm
Dimensions LxWxH	220x70x150 mm	220x70x150 mm	220x70x150 mm	220x70x150 mm
Weight	1.9 kg	1.9 kg	1.9 kg	1.9 kg
<b>Scope of delivery</b>				
Lens cover	✓	✓	✓	✓
Plumb bob	✓	✓	✓	✓
Allen wrench	✓	✓	✓	✓
Adjusting pin	✓	✓	✓	✓
Hard carry case	✓	✓	✓	✓
<b>Suggested Accessories</b>		<b>Part Number</b>		
Bosch Blue BT 160 Professiona Building Tripod		0 601 091 200		